

Hotel Delivery Robot——W3





Key Features

- Industry-leading autonomous navigation solutions to ensure precise localization and movements
- > 3D stereo obstacle avoidance performance with 120° wider viewing angle
- > Automatically lift taking performance ensured by Keenon own robots lift control solution
- Long service time: 9-12 hours uninterrupted service can be provided(actual results may vary)
- > Streamlined design, advanced and rounded to avoid accidental bumping
- > Fully automatic design of cabin opening and closing, designed to prevent pinching hands
- Extra large 90L delivery space with 4 independent compartments to private distribution of multiple items during peak periods
- Extreme Obstacle Crossing Performance: 5 degree climbing capacity, 15mm
 Vertical Height, 30mm Gap Width

Specifications

General

Product Size(W*D*H)	450*550*1080mm
Product Weight	48KG
Number of Cabins	2/3/4
Cabin Size	390*385*300mm
Layer Detachable	Yes
Cabin Load Capacity	20kg (10kg per layer)
Screen Size	11.6 inch
Screen Resolution	1920*1080P
Screen Interactive Mode	light/Touch
Speaker	2 sound tracks
Positioning & Navigation	Laser, IMU, encoder multi-sensor positioning & navigation
Obstacle Avoidance	Dual stereo vision, Anti-collision strips
Sensors	LiDAR, depth vision sensor, and touch sensor
Main Material	ABS Plastic for body
Color Optional	Silver/Champagne gold



Performance

Max Speed	0.8m/s
Battery Endurance	9-12h (assuming 3 deliveries per hour and 5 minutes for each delivery)
Standby Time	Max 15h
Maximum Climbing Angle	Slope≤5°
Overpass Height	Max 15mm
Minimum Pass Width	70cm
Service Life	20000 hours

Battery and charging

Battery Capacity	DC48V 12AH
Battery Dismountable	No
Charging Mode	Auto/Manual
Charging Input	100-240V~,50/60Hz
Charing Time	Approx. 6.5 hours
Charging Pile Dimension	230*220*290 mm
Charging Pile Weight	2.5 KG

Operation Environment


Operating Temperature, Humidity	0 - 45°C, RH: 5% ~ 85%,dust free
Working Environment	Flat and smooth ground indoors
Storage Temperature	0°C-60°C

Others

WIFI	802.11b/g/n transmission
WIFI Frequency	2.4-2.484GHZ
LoRa Frequency	850.125MHz~930.125MHz



Package Content



Battery recharger*1 Charging pile Product Manual*1



Inset Compartment Compartment splitter plate

Main Unit and Dimension





